Building the Glasgow Functional Programming Tools Suite

The GHC Team

The Glasgow fptools suite is a collection of Functional Programming related tools, including the Glasgow Haskell Compiler (GHC). The source code for the whole suite is kept in a single CVS repository and shares a common build and installation system.

This guide is intended for people who want to build or modify programs from the Glasgow `fptools` suite (as distinct from those who merely want to *run* them). Installation instructions are now provided in the user guide.

The bulk of this guide applies to building on Unix systems; see Section 12 for Windows notes.

1. Getting the sources

You can get your hands on the `fptools` in two ways:

Source distributions

> You have a supported platform, but (a) you like the warm fuzzy feeling of compiling things yourself; (b) you want to build something "extra"—e.g., a set of libraries with strictness-analysis turned off; or (c) you want to hack on GHC yourself.
>
> A source distribution contains complete sources for one or more projects in the `fptools` suite. Not only that, but the more awkward machine-independent steps are done for you. For example, if you don't have **happy** you'll find it convenient that the source distribution contains the result of running **happy** on the parser specifications. If you don't want to alter the parser then this saves you having to find and install **happy**. You will still need a working version of GHC (preferably version 4.08+) on your machine in order to compile (most of) the sources, however.

The CVS repository.

> We make releases infrequently. If you want more up-to-the minute (but less tested) source code then you need to get access to our CVS repository.

All the `fptools` source code is held in a CVS repository. CVS is a pretty good source-code control system, and best of all it works over the network.

The repository holds source code only. It holds no mechanically generated files at all. So if you check out a source tree from CVS you will need to install every utility so that you can build all the derived files from scratch.

More information about our CVS repository can be found in Section 2.

If you are going to do any building from sources (either from a source distribution or the CVS repository) then you need to read all of this manual in detail.

2. Using the CVS repository

We use CVS (http://www.cvshome.org/) (Concurrent Version System) to keep track of our sources for various software projects. CVS lets several people work on the same software at the same time, allowing changes to be checked in incrementally.

This section is a set of guidelines for how to use our CVS repository, and will probably evolve in time. The main thing to remember is that most mistakes can be undone, but if there's anything you're not sure about feel free to bug the local CVS meister (namely Jeff Lewis `<jlewis@galconn.com>`).

2.1. Getting access to the CVS Repository

You can access the repository in one of two ways: read-only (Section 2.1.1), or read-write (Section 2.1.2).

2.1.1. Remote Read-only CVS Access

Read-only access is available to anyone - there's no need to ask us first. With read-only CVS access you can do anything except commit changes to the repository. You can make changes to your local tree, and still use CVS's merge facility to keep your tree up to date, and you can generate patches using 'cvs diff' in order to send to us for inclusion.

To get read-only access to the repository:

1. Make sure that cvs is installed on your machine.
2. Set your `$CVSROOT` environment variable to `:pserver:anoncvs@glass.cse.ogi.edu:/cvs`
3. Run the command

```
$ cvs login
```

The password is simply `cvs`. This sets up a file in your home directory called `.cvspass`, which squirrels away the dummy password, so you only need to do this step once.

4. Now go to Section 2.2.

2.1.2. Remote Read-Write CVS Access

We generally supply read-write access to folk doing serious development on some part of the source tree, when going through us would be a pain. If you're developing some feature, or think you have the time and inclination to fix bugs in our sources, feel free to ask for read-write access. There is a certain amount of responsibility that goes with commit privileges; we are more likely to grant you access if you've demonstrated your competence by sending us patches via mail in the past.

To get remote read-write CVS access, you need to do the following steps.

1. Make sure that `cvs` and `ssh` are both installed on your machine.
2. Generate a DSA private-key/public-key pair, thus:

   ```
   $ ssh-keygen -d
   ```

   (`ssh-keygen` comes with `ssh`.) Running `ssh-keygen -d` creates the private and public keys in `$HOME/.ssh/id_dsa` and `$HOME/.ssh/id_dsa.pub` respectively (assuming you accept the standard defaults).

   `ssh-keygen -d` will only work if you have Version 2 `ssh` installed; it will fail harmlessly otherwise. If you only have Version 1 you can instead generate an RSA key pair using plain

   ```
   $ ssh-keygen
   ```

   Doing so creates the private and public RSA keys in `$HOME/.ssh/identity` and `$HOME/.ssh/identity.pub` respectively.

   [Deprecated.] Incidentally, you can force a Version 2 `ssh` to use the Version 1 protocol by creating `$HOME/config` with the following in it:

   ```
   BatchMode Yes

   Host cvs.haskell.org
   Protocol 1
   ```

   In both cases, `ssh-keygen` will ask for a *passphrase*. The passphrase is a password that protects your private key. In response to the 'Enter passphrase' question, you can either:

   - [Recommended.] Enter a passphrase, which you will quote each time you use CVS. `ssh-agent` makes this entirely un-tiresome.
   - [Deprecated.] Just hit return (i.e. use an empty passphrase); then you won't need to quote the passphrase when using CVS. The downside is that anyone who can see into your `.ssh`

directory, and thereby get your private key, can mess up the repository. So you must keep the `.ssh` directory with draconian no-access permissions.

[Windows users.] The programs **ssh-keygen1**, **ssh1**, and **cvs**, seem to lock up **bash** entirely if they try to get user input (e.g. if they ask for a password). To solve this, start up `cmd.exe` and run it as follows:

```
c:\tmp> set CYGWIN32=tty
c:\tmp> c:/user/local/bin/ssh-keygen1
```

[Windows users.] To protect your `.ssh` from access by anyone else, right-click your `.ssh` directory, and select `Properties`. If you are not on the access control list, add yourself, and give yourself full permissions (the second panel). Remove everyone else from the access control list. Don't leave them there but deny them access, because 'they' may be a list that includes you!

3. Send a message to to the CVS repository administrator (currently Jeff Lewis <`jeff@galconn.com`>), containing:

   - Your desired user-name.
   - Your `.ssh/id_dsa.pub` (or `.ssh/identity.pub`).

   He will set up your account.

4. Set the following environment variables:

   - `$HOME`: points to your home directory. This is where CVS will look for its `.cvsrc` file.
   - `$CVS_RSH` to `ssh`

     [Windows users.] Setting your `CVS_RSH` to `ssh` assumes that your CVS client understands how to execute shell script ("#!"s,really), which is what `ssh` is. This may not be the case on Win32 platforms, so in that case set `CVS_RSH` to `ssh1`.

   - `$CVSROOT` to `:ext:`*`your-username`*`@cvs.haskell.org:/home/cvs/root` where *`your-username`* is your user name on `cvs.haskell.org`.

     The `CVSROOT` environment variable will be recorded in the checked-out tree, so you don't need to set this every time.

   - `$CVSEDITOR`: `bin/gnuclient.exe` if you want to use an Emacs buffer for typing in those long commit messages.
   - `$SHELL`: To use bash as the shell in Emacs, you need to set this to point to `bash.exe`.

5. Put the following in `$HOME/.cvsrc`:

   ```
   checkout -P
   release -d
   update -P
   diff -u
   ```

   These are the default options for the specified CVS commands, and represent better defaults than the usual ones. (Feel free to change them.)

   [Windows users.] Filenames starting with `.` were illegal in the 8.3 DOS filesystem, but that restriction should have been lifted by now (i.e., you're using VFAT or later filesystems.) If you're still having problems creating it, don't worry; `.cvsrc` is entirely optional.

[Experts.] Once your account is set up, you can get access from other machines without bothering Jeff, thus:

1. Generate a public/private key pair on the new machine.
2. Use ssh to log in to `cvs.haskell.org`, from your old machine.
3. Add the public key for the new machine to the file `$HOME/ssh/authorized_keys` on `cvs.haskell.org`. (`authorized_keys2`, I think, for Version 2 protocol.)
4. Make sure that the new version of `authorized_keys` still has 600 file permissions.

2.2. Checking Out a Source Tree

- Make sure you set your `CVSROOT` environment variable according to either of the remote methods above. The Approved Way to check out a source tree is as follows:

  ```
  $ cvs checkout fpconfig
  ```

  At this point you have a new directory called `fptools` which contains the basic stuff for the fptools suite, including the configuration files and some other junk.

  [Windows users.] The following messages appear to be harmless:

  ```
  setsockopt IPTOS_LOWDELAY: Invalid argument
  setsockopt IPTOS_THROUGHPUT: Invalid argument
  ```

  You can call the fptools directory whatever you like, CVS won't mind:

  ```
  $ mv fptools directory
  ```

  NB: after you've read the CVS manual you might be tempted to try

  ```
  $ cvs checkout -d directory fpconfig
  ```

instead of checking out `fpconfig` and then renaming it. But this doesn't work, and will result in checking out the entire repository instead of just the `fpconfig` bit.

```
$ cd directory
$ cvs checkout ghc hslibs libraries
```

The second command here checks out the relevant modules you want to work on. For a GHC build, for instance, you need at least the `ghc`, `hslibs` and `libraries` modules (for a full list of the projects available, see Section 3).

2.3. Committing Changes

This is only if you have read-write access to the repository. For anoncvs users, CVS will issue a "read-only repository" error if you try to commit changes.

- Build the software, if necessary. Unless you're just working on documentation, you'll probably want to build the software in order to test any changes you make.
- Make changes. Preferably small ones first.
- Test them. You can see exactly what changes you've made by using the `cvs diff` command:

  ```
  $ cvs diff
  ```

  lists all the changes (using the `diff` command) in and below the current directory. In emacs, `C-c C-v =` runs `cvs diff` on the current buffer and shows you the results.

- Before checking in a change, you need to update your source tree:

  ```
  $ cd fptools
  $ cvs update
  ```

  This pulls in any changes that other people have made, and merges them with yours. If there are any conflicts, CVS will tell you, and you'll have to resolve them before you can check your changes in. The documentation describes what to do in the event of a conflict.

  It's not always necessary to do a full cvs update before checking in a change, since CVS will always tell you if you try to check in a file that someone else has changed. However, you should still update at regular intervals to avoid making changes that don't work in conjuction with changes that someone else made. Keeping an eye on what goes by on the mailing list can help here.

- When you're happy that your change isn't going to break anything, check it in. For a one-file change:

  ```
  $ cvs commit filename
  ```

CVS will then pop up an editor for you to enter a "commit message", this is just a short description of what your change does, and will be kept in the history of the file.

If you're using emacs, simply load up the file into a buffer and type `C-x C-q`, and emacs will prompt for a commit message and then check in the file for you.

For a multiple-file change, things are a bit trickier. There are several ways to do this, but this is the way I find easiest. First type the commit message into a temporary file. Then either

```
$ cvs commit -F commit-message file_1 .... file_n
```

or, if nothing else has changed in this part of the source tree,

```
$ cvs commit -F commit-message directory
```

where *`directory`* is a common parent directory for all your changes, and *`commit-message`* is the name of the file containing the commit message.

Shortly afterwards, you'll get some mail from the relevant mailing list saying which files changed, and giving the commit message. For a multiple-file change, you should still get only *one* message.

2.4. Updating Your Source Tree

It can be tempting to cvs update just part of a source tree to bring in some changes that someone else has made, or before committing your own changes. This is NOT RECOMMENDED! Quite often changes in one part of the tree are dependent on changes in another part of the tree (the `mk/*.mk` files are a good example where problems crop up quite often). Having an inconsistent tree is a major cause of headaches.

So, to avoid a lot of hassle, follow this recipe for updating your tree:

```
$ cd fptools
$ cvs update -Pd 2>&1 | tee log
```

Look at the log file, and fix any conflicts (denoted by a "C" in the first column). If you're using multiple build trees, then for every build tree you have pointing at this source tree, you need to update the links in case any new files have appeared:

```
$ cd build-tree
$ lndir source-tree
```

Some files might have been removed, so you need to remove the links pointing to these non-existent files:

```
$ find . -xtype l -exec rm '{}' \;
```

To be *really* safe, you should do

```
$ gmake all
```

from the top-level, to update the dependencies and build any changed files.

2.5. GHC Tag Policy

If you want to check out a particular version of GHC, you'll need to know how we tag versions in the repository. The policy (as of 4.04) is:

- The tree is branched before every major release. The branch tag is `ghc-x-xx-branch`, where `x-xx` is the version number of the release with the `'.'` replaced by a `'-'`. For example, the 4.04 release lives on `ghc-4-04-branch`.
- The release itself is tagged with `ghc-x-xx` (on the branch). eg. 4.06 is called `ghc-4-06`.
- We didn't always follow these guidelines, so to see what tags there are for previous versions, do `cvs log` on a file that's been around for a while (like `fptools/ghc/README`).

So, to check out a fresh GHC 4.06 tree you would do:

```
$ cvs co -r ghc-4-06 fpconfig
$ cd fptools
$ cvs co -r ghc-4-06 ghc hslibs
```

2.6. General Hints

- As a general rule: commit changes in small units, preferably addressing one issue or implementing a single feature. Provide a descriptive log message so that the repository records exactly which changes were required to implement a given feature/fix a bug. I've found this *very* useful in the past for finding out when a particular bug was introduced: you can just wind back the CVS tree until the bug disappears.
- Keep the sources at least *buildable* at any given time. No doubt bugs will creep in, but it's quite easy to ensure that any change made at least leaves the tree in a buildable state. We do nightly builds of GHC to keep an eye on what things work/don't work each day and how we're doing in relation to previous verions. This idea is truely wrecked if the compiler won't build in the first place!
- To check out extra bits into an already-checked-out tree, use the following procedure. Suppose you have a checked-out fptools tree containing just ghc, and you want to add nofib to it:

  ```
  $ cd fptools
  $ cvs checkout nofib
  ```

  or:

  ```
  $ cd fptools
  $ cvs update -d nofib
  ```

(the -d flag tells update to create a new directory). If you just want part of the nofib suite, you can do

```
$ cd fptools
$ cvs checkout nofib/spectral
```

This works because `nofib` is a module in its own right, and spectral is a subdirectory of the nofib module. The path argument to checkout must always start with a module name. There's no equivalent form of this command using `update`.

3. What projects are there?

The `fptools` suite consists of several *projects*, most of which can be downloaded, built and installed individually. Each project corresponds to a subdirectory in the source tree, and if checking out from CVS then each project can be checked out individually by sitting in the top level of your source tree and typing **cvs checkout *`project`***.

Here is a list of the projects currently available:

`ghc`

The Glasgow Haskell Compiler (http://www.haskell.org/ghc/) (minus libraries). Absolutely required for building GHC.

`glafp-utils`

Utility programs, some of which are used by the build/installation system. Required for pretty much everything.

`green-card`

The Green Card (http://www.haskell.org/greencard/) system for generating Haskell foreign function interfaces.

`haggis`

The Haggis (http://www.dcs.gla.ac.uk/fp/software/haggis/) Haskell GUI framework.

`haddock`

The Haddock (http://www.haskell.org/haddock/) documentation tool.

`happy`

The Happy (http://www.haskell.org/happy/) Parser generator.

`hdirect`

The H/Direct (http://www.haskell.org/hdirect/) Haskell interoperability tool.

`hood`

The Haskell Object Observation Debugger (http://www.haskell.org/hood/).

`hslibs`

Supplemental libraries for GHC (*required* for building GHC).

`libraries`

Hierarchical Haskell library suite (*required* for building GHC).

`mhms`

The Modular Haskell Metric System.

`nofib`

The NoFib suite: A collection of Haskell programs used primarily for benchmarking.

`testsuite`

A testing framework, including GHC's regression test suite.

So, to build GHC you need at least the `ghc`, `libraries` and `hslibs` projects (a GHC source distribution will already include the bits you need).

4. Things to check before you start

Here's a list of things to check before you get started.

1. Disk space needed: from about 100Mb for a basic GHC build, up to probably 500Mb for a GHC build with everything included (libraries built several different ways, etc.).

2. Use an appropriate machine / operating system. Section 5 lists the supported platforms; if yours isn't amongst these then you can try porting GHC (see Section 10).
3. Be sure that the "pre-supposed" utilities are installed. Section 6 elaborates.
4. If you have any problem when building or installing the Glasgow tools, please check the "known pitfalls" (Section 11). Also check the FAQ for the version you're building, which is part of the User's Guide and available on the GHC web site (http://www.haskell.org/ghc/).

   If you feel there is still some shortcoming in our procedure or instructions, please report it.

For GHC, please see the bug-reporting section of the GHC Users' Guide (http://www.haskell.org/ghc/docs/latest/set/bug-reporting.html), to maximise the usefulness of your report.

If in doubt, please send a message to `<glasgow-haskell-bugs@haskell.org>`.

5. What machines the Glasgow tools run on

The main question is whether or not the Haskell compiler (GHC) runs on your platform.

A "platform" is a architecture/manufacturer/operating-system combination, such as `sparc-sun-solaris2`. Other common ones are `alpha-dec-osf2`, `hppa1.1-hp-hpux9`, `i386-unknown-linux`, `i386-unknown-solaris2`, `i386-unknown-freebsd`, `i386-unknown-cygwin32`, `m68k-sun-sunos4`, `mips-sgi-irix5`, `sparc-sun-sunos4`, `sparc-sun-solaris2`, `powerpc-ibm-aix`.

Some libraries may only work on a limited number of platforms; for example, a sockets library is of no use unless the operating system supports the underlying BSDisms.

5.1. What platforms the Haskell compiler (GHC) runs on

The GHC hierarchy of Porting Goodness: (a) Best is a native-code generator; (b) next best is a "registerised" port; (c) the bare minimum is an "unregisterised" port. ("Unregisterised" is so terrible that we won't say more about it).

We use Sparcs running Solaris 2.7 and x86 boxes running FreeBSD and Linux, so those are the best supported platforms, unsurprisingly.

Here's everything that's known about GHC ports. We identify platforms by their "canonical" CPU/Manufacturer/OS triple.

alpha-dec-{osf,linux,freebsd,openbsd,netbsd}:

> The OSF port is currently working (as of GHC version 5.02.1) and well supported. The native code generator is currently non-working. Other operating systems will require some minor porting.

sparc-sun-sunos4

> Probably works with minor tweaks, hasn't been tested for a while.

sparc-sun-solaris2

> Fully supported (at least for Solaris 2.7), including native-code generator.

hppa1.1-hp-hpux (HP-PA boxes running HPUX 9.x)

A registerised port is available for version 4.08, but GHC hasn't been built on that platform since (as far as we know). No native-code generator.

i386-unknown-linux (PCs running Linux, ELF binary format)

GHC works registerised and has a native code generator. You *must* have GCC 2.7.x or later. NOTE about `glibc` versions: GHC binaries built on a system running `glibc 2.0` won't work on a system running `glibc 2.1`, and vice versa. In general, don't expect compatibility between `glibc` versions, even if the shared library version hasn't changed.

i386-unknown-freebsd (PCs running FreeBSD 2.2 or higher)

GHC works registerised. Pre-built packages are available in the native package format, so if you just need binaries you're better off just installing the package (it might even be on your installation CD!).

i386-unknown-openbsd (PCs running OpenBSD)

Supported, with native code generator. Packages are available through the ports system in the native package format.

i386-unknown-netbsd (PCs running NetBSD and OpenBSD)

Will require some minor porting effort, but should work registerised.

i386-unknown-mingw32 (PCs running Windows)

Fully supported under Win9x, WinNT, Win2k, and WinXP. Includes a native code generator. Building from source requires a recent Cygwin (http://www.cygwin.com/) distribution to be installed.

ia64-unknown-linux

GHC currently works unregisterised. A registerised port is in progress.

mips-sgi-irix5

Port has worked in the past, but hasn't been tested for some time (and will certainly have rotted in various ways). As usual, we don't have access to machines and there hasn't been an overwhelming demand for this port, but feel free to get in touch.

powerpc-ibm-aix

Port currently doesn't work, needs some minimal porting effort. As usual, we don't have access to machines and there hasn't been an overwhelming demand for this port, but feel free to get in touch.

powerpc-apple-darwin

Supported registerised. No native code generator.

powerpc-apple-linux

Not supported (yet).

Various other systems have had GHC ported to them in the distant past, including various Motorola 68k boxes. The 68k support still remains, but porting to one of these systems will certainly be a non-trivial task.

5.2. What machines the other tools run on

Unless you hear otherwise, the other tools work if GHC works.

6. Installing pre-supposed utilities

Here are the gory details about some utility programs you may need; **perl**, **gcc** and **happy** are the only important ones. (PVM is important if you're going for Parallel Haskell.) The **configure** script will tell you if you are missing something.

GHC

GHC is required to build many of the tools, including GHC itself. If you need to port GHC to your platform because there isn't a binary distribution of GHC available, then see Section 10.

Which version of GHC you need will depend on the packages you intend to build. GHC itself will normally build using one of several older versions of itself - check the announcement or release notes for details.

Perl

You have to have Perl to proceed! Perl version 5 at least is required. GHC has been known to tickle bugs in Perl, so if you find that Perl crashes when running GHC try updating (or downgrading) your Perl installation. Versions of Perl that we use and are known to be fairly stable are 5.005 and 5.6.1.

For Win32 platforms, you should use the binary supplied in the InstallShield (copy it to `/bin`). The Cygwin-supplied Perl seems not to work.

Perl should be put somewhere so that it can be invoked by the `#!` script-invoking mechanism. The full pathname may need to be less than 32 characters long on some systems.

GNU C (**gcc**)

We recommend using GCC version 2.95.2 on all platforms. Failing that, version 2.7.2 is stable on most platforms. Earlier versions of GCC can be assumed not to work, and versions in between 2.7.2 and 2.95.2 (including **egcs**) have varying degrees of stability depending on the platform.

If your GCC dies with "internal error" on some GHC source file, please let us know, so we can report it and get things improved. (Exception: on iX86 boxes—you may need to fiddle with GHC's `-monly-N-regs` option; see the User's Guide)

GNU Make

The fptools build system makes heavy use of features specific to GNU **make**, so you must have this installed in order to build any of the fptools suite.

Happy

Happy is a parser generator tool for Haskell, and is used to generate GHC's parsers. Happy is written in Haskell, and is a project in the CVS repository (`fptools/happy`). It can be built from source, but bear in mind that you'll need GHC installed in order to build it. To avoid the chicken/egg problem, install a binary distribtion of either Happy or GHC to get started. Happy distributions are available from Happy's Web Page (http://www.haskell.org/happy/).

Autoconf

GNU Autoconf is needed if you intend to build from the CVS sources, it is *not* needed if you just intend to build a standard source distribution.

Autoconf builds the **configure** script from `configure.in` and `aclocal.m4`. If you modify either of these files, you'll need **autoconf** to rebuild `configure`.

sed

You need a working **sed** if you are going to build from sources. The build-configuration stuff needs it. GNU sed version 2.0.4 is no good! It has a bug in it that is tickled by the build-configuration. 2.0.5 is OK. Others are probably OK too (assuming we don't create too elaborate configure scripts.)

One `fptools` project is worth a quick note at this point, because it is useful for all the others: `glafp-utils` contains several utilities which aren't particularly Glasgow-ish, but Occasionally Indispensable. Like **lndir** for creating symbolic link trees.

6.1. Tools for building parallel GHC (GPH)

PVM version 3:

PVM is the Parallel Virtual Machine on which Parallel Haskell programs run. (You only need this if you plan to run Parallel Haskell. Concurent Haskell, which runs concurrent threads on a uniprocessor doesn't need it.) Underneath PVM, you can have (for example) a network of workstations (slow) or a multiprocessor box (faster).

The current version of PVM is 3.3.11; we use 3.3.7. It is readily available on the net; I think I got it from `research.att.com`, in `netlib`.

A PVM installation is slightly quirky, but easy to do. Just follow the `Readme` instructions.

bash:

Sadly, the **gr2ps** script, used to convert "parallelism profiles" to PostScript, is written in Bash (GNU's Bourne Again shell). This bug will be fixed (someday).

6.2. Other useful tools

Flex

This is a quite-a-bit-better-than-Lex lexer. Used to build a couple of utilities in `glafp-utils`. Depending on your operating system, the supplied **lex** may or may not work; you should get the GNU version.

More tools are required if you want to format the documentation that comes with GHC and other fptools projects. See Section 9.

7. Building from source

You've been rash enough to want to build some of the Glasgow Functional Programming tools (GHC, Happy, nofib, etc.) from source. You've slurped the source, from the CVS repository or from a source distribution, and now you're sitting looking at a huge mound of bits, wondering what to do next.

Gingerly, you type **make**. Wrong already!

This rest of this guide is intended for duffers like me, who aren't really interested in Makefiles and systems configurations, but who need a mental model of the interlocking pieces so that they can make them work, extend them consistently when adding new software, and lay hands on them gently when they don't work.

7.1. Your source tree

The source code is held in your *source tree*. The root directory of your source tree *must* contain the following directories and files:

- `Makefile`: the root Makefile.
- `mk/`: the directory that contains the main Makefile code, shared by all the `fptools` software.
- `configure.in`, `config.sub`, `config.guess`: these files support the configuration process.
- `install-sh`.

All the other directories are individual *projects* of the `fptools` system—for example, the Glasgow Haskell Compiler (`ghc`), the Happy parser generator (`happy`), the `nofib` benchmark suite, and so on. You can have zero or more of these. Needless to say, some of them are needed to build others.

The important thing to remember is that even if you want only one project (`happy`, say), you must have a source tree whose root directory contains `Makefile`, `mk/`, `configure.in`, and the project(s) you want (`happy/` in this case). You cannot get by with just the `happy/` directory.

7.2. Build trees

If you just want to build the software once on a single platform, then your source tree can also be your build tree, and you can skip the rest of this section.

We often want to build multiple versions of our software for different architectures, or with different options (e.g. profiling). It's very desirable to share a single copy of the source code among all these builds.

So for every source tree we have zero or more *build trees*. Each build tree is initially an exact copy of the source tree, except that each file is a symbolic link to the source file, rather than being a copy of the source file. There are "standard" Unix utilities that make such copies, so standard that they go by different names: **lndir**, **mkshadowdir** are two (If you don't have either, the source distribution includes sources for the X11 **lndir**—check out `fptools/glafp-utils/lndir`). See Section 7.4 for a typical invocation.

The build tree does not need to be anywhere near the source tree in the file system. Indeed, one advantage of separating the build tree from the source is that the build tree can be placed in a non-backed-up partition, saving your systems support people from backing up untold megabytes of easily-regenerated, and rapidly-changing, gubbins. The golden rule is that (with a single exception—Section 7.3) *absolutely everything in the build tree is either a symbolic link to the source tree, or else is mechanically generated*. It should be perfectly OK for your build tree to vanish overnight; an hour or two compiling and you're on the road again.

You need to be a bit careful, though, that any new files you create (if you do any development work) are in the source tree, not a build tree!

Remember, that the source files in the build tree are *symbolic links* to the files in the source tree. (The build tree soon accumulates lots of built files like `Foo.o`, as well.) You can *delete* a source file from

the build tree without affecting the source tree (though it's an odd thing to do). On the other hand, if you *edit* a source file from the build tree, you'll edit the source-tree file directly. (You can set up Emacs so that if you edit a source file from the build tree, Emacs will silently create an edited copy of the source file in the build tree, leaving the source file unchanged; but the danger is that you think you've edited the source file whereas actually all you've done is edit the build-tree copy. More commonly you do want to edit the source file.)

Like the source tree, the top level of your build tree must be (a linked copy of) the root directory of the `fptools` suite. Inside Makefiles, the root of your build tree is called `$(FPTOOLS_TOP)`. In the rest of this document path names are relative to `$(FPTOOLS_TOP)` unless otherwise stated. For example, the file `ghc/mk/target.mk` is actually `$(FPTOOLS_TOP)/ghc/mk/target.mk`.

7.3. Getting the build you want

When you build `fptools` you will be compiling code on a particular *host platform*, to run on a particular *target platform* (usually the same as the host platform). The difficulty is that there are minor differences between different platforms; minor, but enough that the code needs to be a bit different for each. There are some big differences too: for a different architecture we need to build GHC with a different native-code generator.

There are also knobs you can turn to control how the `fptools` software is built. For example, you might want to build GHC optimised (so that it runs fast) or unoptimised (so that you can compile it fast after you've modified it. Or, you might want to compile it with debugging on (so that extra consistency-checking code gets included) or off. And so on.

All of this stuff is called the *configuration* of your build. You set the configuration using a three-step process.

Step 1: get ready for configuration.

Change directory to `$(FPTOOLS_TOP)` and issue the command **autoconf** (with no arguments). This GNU program converts `$(FPTOOLS_TOP)/configure.in` to a shell script called `$(FPTOOLS_TOP)/configure`.

Some projects, including GHC, have their own configure script. If there's an `$(FPTOOLS_TOP)/<project>/configure.in`, then you need to run **autoconf** in that directory too.

Both these steps are completely platform-independent; they just mean that the human-written file (`configure.in`) can be short, although the resulting shell script, **configure**, and `mk/config.h.in`, are long.

In case you don't have **autoconf** we distribute the results, **configure**, and `mk/config.h.in`, with the source distribution. They aren't kept in the repository, though.

Step 2: system configuration.

Runs the newly-created **configure** script, thus:

`./configure [`*`args`*`]`

configure's mission is to scurry round your computer working out what architecture it has, what operating system, whether it has the `vfork` system call, where **yacc** is kept, whether **gcc** is available, where various obscure `#include` files are, whether it's a leap year, and what the systems manager had for lunch. It communicates these snippets of information in two ways:

- It translates `mk/config.mk.in` to `mk/config.mk`, substituting for things between "`@`" brackets. So, "`@HaveGcc@`" will be replaced by "`YES`" or "`NO`" depending on what **configure** finds. `mk/config.mk` is included by every Makefile (directly or indirectly), so the configuration information is thereby communicated to all Makefiles.
- It translates `mk/config.h.in` to `mk/config.h`. The latter is `#included` by various C programs, which can thereby make use of configuration information.

configure takes some optional arguments. Use `./configure --help` to get a list of the available arguments. Here are some of the ones you might need:

`--with-ghc=`*`path`*

Specifies the path to an installed GHC which you would like to use. This compiler will be used for compiling GHC-specific code (eg. GHC itself). This option *cannot* be specified using `build.mk` (see later), because **configure** needs to auto-detect the version of GHC you're using. The default is to look for a compiler named `ghc` in your path.

`--with-hc=`*`path`*

Specifies the path to any installed Haskell compiler. This compiler will be used for compiling generic Haskell code. The default is to use `ghc`.

`--with-gcc=`*`path`*

Specifies the path to the installed GCC. This compiler will be used to compile all C files, *except* any generated by the installed Haskell compiler, which will have its own idea of which C compiler (if any) to use. The default is to use `gcc`.

configure caches the results of its run in `config.cache`. Quite often you don't want that; you're running **configure** a second time because something has changed. In that case, simply delete `config.cache`.

Step 3: build configuration.

Next, you say how this build of `fptools` is to differ from the standard defaults by creating a new file `mk/build.mk` *in the build tree*. This file is the one and only file you edit in the build tree, precisely because it says how this build differs from the source. (Just in case your build tree

does die, you might want to keep a private directory of `build.mk` files, and use a symbolic link in each build tree to point to the appropriate one.) So `mk/build.mk` never exists in the source tree—you create one in each build tree from the template. We'll discuss what to put in it shortly.

And that's it for configuration. Simple, eh?

What do you put in your build-specific configuration file `mk/build.mk`? *For almost all purposes all you will do is put make variable definitions that override those in* `mk/config.mk.in`. The whole point of `mk/config.mk.in`—and its derived counterpart `mk/config.mk`—is to define the build configuration. It is heavily commented, as you will see if you look at it. So generally, what you do is look at `mk/config.mk.in`, and add definitions in `mk/build.mk` that override any of the `config.mk` definitions that you want to change. (The override occurs because the main boilerplate file, `mk/boilerplate.mk`, includes `build.mk` after `config.mk`.)

For example, `config.mk.in` contains the definition:

```
GhcHcOpts=-O -Rghc-timing
```

The accompanying comment explains that this is the list of flags passed to GHC when building GHC itself. For doing development, it is wise to add `-DDEBUG`, to enable debugging code. So you would add the following to `build.mk`:

or, if you prefer,

```
GhcHcOpts += -DDEBUG
```

GNU **make** allows existing definitions to have new text appended using the "+=" operator, which is quite a convenient feature.)

If you want to remove the `-O` as well (a good idea when developing, because the turn-around cycle gets a lot quicker), you can just override `GhcLibHcOpts` altogether:

```
GhcHcOpts=-DDEBUG -Rghc-timing
```

When reading `config.mk.in`, remember that anything between "@...@" signs is going to be substituted by **configure** later. You *can* override the resulting definition if you want, but you need to be a bit surer what you are doing. For example, there's a line that says:

```
YACC = @YaccCmd@
```

This defines the Make variables `YACC` to the pathname for a **yacc** that **configure** finds somewhere. If you have your own pet **yacc** you want to use instead, that's fine. Just add this line to `mk/build.mk`:

```
YACC = myyacc
```

You do not *have* to have a `mk/build.mk` file at all; if you don't, you'll get all the default settings from `mk/config.mk.in`.

You can also use `build.mk` to override anything that **configure** got wrong. One place where this happens often is with the definition of `FPTOOLS_TOP_ABS`: this variable is supposed to be the canonical path to the top of your source tree, but if your system uses an automounter then the correct

directory is hard to find automatically. If you find that **configure** has got it wrong, just put the correct definition in `build.mk`.

7.4. The story so far

Let's summarise the steps you need to carry to get yourself a fully-configured build tree from scratch.

1. Get your source tree from somewhere (CVS repository or source distribution). Say you call the root directory `myfptools` (it does not have to be called `fptools`). Make sure that you have the essential files (see Section 7.1).

2. (Optional) Use **lndir** or **mkshadowdir** to create a build tree.

   ```
   $ cd myfptools
   $ mkshadowdir . /scratch/joe-bloggs/myfptools-sun4
   ```

   (N.B. **mkshadowdir**'s first argument is taken relative to its second.) You probably want to give the build tree a name that suggests its main defining characteristic (in your mind at least), in case you later add others.

3. Change directory to the build tree. Everything is going to happen there now.

   ```
   $ cd /scratch/joe-bloggs/myfptools-sun4
   ```

4. Prepare for system configuration:

   ```
   $ autoconf
   ```

   (You can skip this step if you are starting from a source distribution, and you already have `configure` and `mk/config.h.in`.)

   Some projects, including GHC itself, have their own configure scripts, so it is necessary to run autoconf again in the appropriate subdirectories. eg:

   ```
   $ (cd ghc; autoconf)
   ```

5. Do system configuration:

   ```
   $ ./configure
   ```

   Don't forget to check whether you need to add any arguments to `configure`; for example, a common requirement is to specify which GHC to use with `--with-ghc=`*`ghc`*.

6. Create the file `mk/build.mk`, adding definitions for your desired configuration options.

   ```
   $ emacs mk/build.mk
   ```

You can make subsequent changes to `mk/build.mk` as often as you like. You do not have to run any further configuration programs to make these changes take effect. In theory you should, however, say **gmake clean**, **gmake all**, because configuration option changes could affect anything—but in practice you are likely to know what's affected.

7.5. Making things

At this point you have made yourself a fully-configured build tree, so you are ready to start building real things.

The first thing you need to know is that *you must use GNU **make**, usually called **gmake**, not standard Unix **make***. If you use standard Unix **make** you will get all sorts of error messages (but no damage) because the `fptools` **Makefiles** use GNU **make**'s facilities extensively.

To just build the whole thing, **cd** to the top of your `fptools` tree and type **gmake**. This will prepare the tree and build the various projects in the correct order.

7.6. Standard Targets

In any directory you should be able to make the following:

`boot`

does the one-off preparation required to get ready for the real work. Notably, it does **gmake depend** in all directories that contain programs. It also builds the necessary tools for compilation to proceed.

Invoking the `boot` target explicitly is not normally necessary. From the top-level `fptools` directory, invoking `gmake` causes `gmake boot all` to be invoked in each of the project subdirectories, in the order specified by `$(AllTargets)` in `config.mk`.

If you're working in a subdirectory somewhere and need to update the dependencies, `gmake boot` is a good way to do it.

`all`

makes all the final target(s) for this Makefile. Depending on which directory you are in a "final target" may be an executable program, a library archive, a shell script, or a Postscript file. Typing **gmake** alone is generally the same as typing **gmake all**.

`install`

installs the things built by `all` (except for the documentation). Where does it install them? That is specified by `mk/config.mk.in`; you can override it in `mk/build.mk`, or by running

configure with command-line arguments like `--bindir=/home/simonpj/bin`; see `./configure --help` for the full details.

`install-docs`

installs the documentation. Otherwise behaves just like `install`.

`uninstall`

reverses the effect of `install`.

`clean`

Delete all files from the current directory that are normally created by building the program. Don't delete the files that record the configuration, or files generated by **gmake boot**. Also preserve files that could be made by building, but normally aren't because the distribution comes with them.

`distclean`

Delete all files from the current directory that are created by configuring or building the program. If you have unpacked the source and built the program without creating any other files, `make distclean` should leave only the files that were in the distribution.

`mostlyclean`

Like `clean`, but may refrain from deleting a few files that people normally don't want to recompile.

`maintainer-clean`

Delete everything from the current directory that can be reconstructed with this Makefile. This typically includes everything deleted by `distclean`, plus more: C source files produced by Bison, tags tables, Info files, and so on.

One exception, however: `make maintainer-clean` should not delete `configure` even if `configure` can be remade using a rule in the `Makefile`. More generally, `make maintainer-clean` should not delete anything that needs to exist in order to run `configure` and then begin to build the program.

`check`

run the test suite.

All of these standard targets automatically recurse into sub-directories. Certain other standard targets do not:

`configure`

is only available in the root directory `$(FPTOOLS_TOP)`; it has been discussed in Section 7.3.

`depend`

make a `.depend` file in each directory that needs it. This `.depend` file contains mechanically-generated dependency information; for example, suppose a directory contains a Haskell source module `Foo.lhs` which imports another module `Baz`. Then the generated `.depend` file will contain the dependency:

```
Foo.o : Baz.hi
```

which says that the object file `Foo.o` depends on the interface file `Baz.hi` generated by compiling module `Baz`. The `.depend` file is automatically included by every Makefile.

`binary-dist`

make a binary distribution. This is the target we use to build the binary distributions of GHC and Happy.

`dist`

make a source distribution. Note that this target does "make distclean" as part of its work; don't use it if you want to keep what you've built.

Most `Makefiles` have targets other than these. You can discover them by looking in the `Makefile` itself.

7.7. Using a project from the build tree

If you want to build GHC (say) and just use it direct from the build tree without doing `make install` first, you can run the in-place driver script: `ghc/compiler/ghc-inplace`.

Do *NOT* use `ghc/compiler/ghc`, or `ghc/compiler/ghc-5.xx`, as these are the scripts intended for installation, and contain hard-wired paths to the installed libraries, rather than the libraries in the build tree.

Happy can similarly be run from the build tree, using `happy/src/happy-inplace`.

7.8. Fast Making

Sometimes the dependencies get in the way: if you've made a small change to one file, and you're absolutely sure that it won't affect anything else, but you know that **make** is going to rebuild everything anyway, the following hack may be useful:

```
gmake FAST=YES
```

This tells the make system to ignore dependencies and just build what you tell it to. In other words, it's equivalent to temporarily removing the `.depend` file in the current directory (where **mkdependHS** and friends store their dependency information).

A bit of history: GHC used to come with a **fastmake** script that did the above job, but GNU make provides the features we need to do it without resorting to a script. Also, we've found that fastmaking is less useful since the advent of GHC's recompilation checker (see the User's Guide section on "Separate Compilation").

8. The `Makefile` architecture

make is great if everything works—you type **gmake install** and lo! the right things get compiled and installed in the right places. Our goal is to make this happen often, but somehow it often doesn't; instead some weird error message eventually emerges from the bowels of a directory you didn't know existed.

The purpose of this section is to give you a road-map to help you figure out what is going right and what is going wrong.

8.1. Debugging

Debugging `Makefile`s is something of a black art, but here's a couple of tricks that we find particularly useful. The following command allows you to see the contents of any make variable in the context of the current `Makefile`:

```
$  make show VALUE=HS_SRCS
```

where you can replace `HS_SRCS` with the name of any variable you wish to see the value of.

GNU make has a `-d` option which generates a dump of the decision procedure used to arrive at a conclusion about which files should be recompiled. Sometimes useful for tracking down problems with superfluous or missing recompilations.

8.2. A small project

To get started, let us look at the `Makefile` for an imaginary small `fptools` project, `small`. Each project in `fptools` has its own directory in `FPTOOLS_TOP`, so the `small` project will have its own directory `FPOOLS_TOP/small/`. Inside the `small/` directory there will be a `Makefile`, looking something like this:

```
#     Makefile for fptools project "small"

TOP = ..
include $(TOP)/mk/boilerplate.mk

SRCS = $(wildcard *.lhs) $(wildcard *.c)
HS_PROG = small
```

```
include $(TOP)/target.mk
```

this `Makefile` has three sections:

1. The first section includes [1] a file of "boilerplate" code from the level above (which in this case will be `FPTOOLS_TOP/mk/boilerplate.mk`). As its name suggests, `boilerplate.mk` consists of a large quantity of standard `Makefile` code. We discuss this boilerplate in more detail in Section 8.5.

   Before the `include` statement, you must define the **make** variable `TOP` to be the directory containing the `mk` directory in which the `boilerplate.mk` file is. It is *not* OK to simply say

   ```
   include ../mk/boilerplate.mk  # NO NO NO
   ```

   Why? Because the `boilerplate.mk` file needs to know where it is, so that it can, in turn, `include` other files. (Unfortunately, when an `included` file does an `include`, the filename is treated relative to the directory in which **gmake** is being run, not the directory in which the `included` sits.) In general, *every file `foo.mk` assumes that `$(TOP)/mk/foo.mk` refers to itself.* It is up to the `Makefile` doing the `include` to ensure this is the case.

   Files intended for inclusion in other `Makefile`s are written to have the following property: *after `foo.mk` is `included`, it leaves `TOP` containing the same value as it had just before the `include` statement*. In our example, this invariant guarantees that the `include` for `target.mk` will look in the same directory as that for `boilerplate.mk`.

2. The second section defines the following standard **make** variables: `SRCS` (the source files from which is to be built), and `HS_PROG` (the executable binary to be built). We will discuss in more detail what the "standard variables" are, and how they affect what happens, in Section 8.7.

   The definition for `SRCS` uses the useful GNU **make** construct `$(wildcard $pat$)`, which expands to a list of all the files matching the pattern `pat` in the current directory. In this example, `SRCS` is set to the list of all the `.lhs` and `.c` files in the directory. (Let's suppose there is one of each, `Foo.lhs` and `Baz.c`.)

3. The last section includes a second file of standard code, called `target.mk`. It contains the rules that tell **gmake** how to make the standard targets (Section 7.6). Why, you ask, can't this standard code be part of `boilerplate.mk`? Good question. We discuss the reason later, in Section 8.4.

   You do not *have* to `include` the `target.mk` file. Instead, you can write rules of your own for all the standard targets. Usually, though, you will find quite a big payoff from using the canned rules in `target.mk`; the price tag is that you have to understand what canned rules get enabled, and what they do (Section 8.7).

In our example `Makefile`, most of the work is done by the two `included` files. When you say **gmake all**, the following things happen:

- **gmake** figures out that the object files are `Foo.o` and `Baz.o`.
- It uses a boilerplate pattern rule to compile `Foo.lhs` to `Foo.o` using a Haskell compiler. (Which one? That is set in the build configuration.)
- It uses another standard pattern rule to compile `Baz.c` to `Baz.o`, using a C compiler. (Ditto.)
- It links the resulting `.o` files together to make `small`, using the Haskell compiler to do the link step. (Why not use **ld**? Because the Haskell compiler knows what standard libraries to link in. How did **gmake** know to use the Haskell compiler to do the link, rather than the C compiler? Because we set the variable `HS_PROG` rather than `C_PROG`.)

All `Makefile`s should follow the above three-section format.

8.3. A larger project

Larger projects are usually structured into a number of sub-directories, each of which has its own `Makefile`. (In very large projects, this sub-structure might be iterated recursively, though that is rare.) To give you the idea, here's part of the directory structure for the (rather large) GHC project:

```
$(FPTOOLS_TOP)/ghc/
  Makefile
  mk/
    boilerplate.mk
    rules.mk
   docs/
    Makefile
    ...source files for documentation...
   driver/
    Makefile
    ...source files for driver...
   compiler/
    Makefile
    parser/...source files for parser...
    renamer/...source files for renamer...
    ...etc...
```

The sub-directories `docs`, `driver`, `compiler`, and so on, each contains a sub-component of GHC, and each has its own `Makefile`. There must also be a `Makefile` in `$(FPTOOLS_TOP)/ghc`. It does most of its work by recursively invoking **gmake** on the `Makefile`s in the sub-directories. We say that `ghc/Makefile` is a *non-leaf `Makefile`*, because it does little except organise its children, while the `Makefile`s in the sub-directories are all *leaf `Makefiles`*. (In principle the sub-directories might themselves contain a non-leaf `Makefile` and several sub-sub-directories, but that does not happen in GHC.)

The `Makefile` in `ghc/compiler` is considered a leaf `Makefile` even though the `ghc/compiler` has sub-directories, because these sub-directories do not themselves have `Makefile`s in them. They

are just used to structure the collection of modules that make up GHC, but all are managed by the single `Makefile` in `ghc/compiler`.

You will notice that `ghc/` also contains a directory `ghc/mk/`. It contains GHC-specific `Makefile` boilerplate code. More precisely:

- `ghc/mk/boilerplate.mk` is included at the top of `ghc/Makefile`, and of all the leaf `Makefile`s in the sub-directories. It in turn `include`s the main boilerplate file `mk/boilerplate.mk`.
- `ghc/mk/target.mk` is `include`d at the bottom of `ghc/Makefile`, and of all the leaf `Makefile`s in the sub-directories. It in turn `include`s the file `mk/target.mk`.

So these two files are the place to look for GHC-wide customisation of the standard boilerplate.

8.4. Boilerplate architecture

Every `Makefile` includes a `boilerplate.mk` file at the top, and `target.mk` file at the bottom. In this section we discuss what is in these files, and why there have to be two of them. In general:

- `boilerplate.mk` consists of:
  - *Definitions of millions of **make** variables* that collectively specify the build configuration. Examples: `HC_OPTS`, the options to feed to the Haskell compiler; `NoFibSubDirs`, the sub-directories to enable within the `nofib` project; `GhcWithHc`, the name of the Haskell compiler to use when compiling GHC in the `ghc` project.
  - *Standard pattern rules* that tell **gmake** how to construct one file from another.

  `boilerplate.mk` needs to be `include`d at the *top* of each `Makefile`, so that the user can replace the boilerplate definitions or pattern rules by simply giving a new definition or pattern rule in the `Makefile`. **gmake** simply takes the last definition as the definitive one.

  Instead of *replacing* boilerplate definitions, it is also quite common to *augment* them. For example, a `Makefile` might say:

  ```
  SRC_HC_OPTS += -O
  ```

  thereby adding "`-O`" to the end of `SRC_HC_OPTS`.

- `target.mk` contains **make** rules for the standard targets described in Section 7.6. These rules are selectively included, depending on the setting of certain **make** variables. These variables are usually set in the middle section of the `Makefile` between the two `include`s.

  `target.mk` must be included at the end (rather than being part of `boilerplate.mk`) for several tiresome reasons:

- **gmake** commits target and dependency lists earlier than it should. For example, `target.mk` has a rule that looks like this:

  ```
  $(HS_PROG) : $(OBJS)
        $(HC) $(LD_OPTS) $< -o $@
  ```

  If this rule was in `boilerplate.mk` then `$(HS_PROG)` and `$(OBJS)` would not have their final values at the moment **gmake** encountered the rule. Alas, **gmake** takes a snapshot of their current values, and wires that snapshot into the rule. (In contrast, the commands executed when the rule "fires" are only substituted at the moment of firing.) So, the rule must follow the definitions given in the `Makefile` itself.

- Unlike pattern rules, ordinary rules cannot be overriden or replaced by subsequent rules for the same target (at least, not without an error message). Including ordinary rules in `boilerplate.mk` would prevent the user from writing rules for specific targets in specific cases.
- There are a couple of other reasons I've forgotten, but it doesn't matter too much.

8.5. The main `mk/boilerplate.mk` file

If you look at `$(FPTOOLS_TOP)/mk/boilerplate.mk` you will find that it consists of the following sections, each held in a separate file:

`config.mk`

is the build configuration file we discussed at length in Section 7.3.

`paths.mk`

defines **make** variables for pathnames and file lists. This file contains code for automatically compiling lists of source files and deriving lists of object files from those. The results can be overriden in the `Makefile`, but in most cases the automatic setup should do the right thing.

The following variables may be set in the `Makefile` to affect how the automatic source file search is done:

`ALL_DIRS`

Set to a list of directories to search in addition to the current directory for source files.

`EXCLUDE_SRCS`

Set to a list of source files (relative to the current directory) to omit from the automatic search. The source searching machinery is clever enough to know that if you exclude a source file from which other sources are derived, then the derived sources should also be

excluded. For example, if you set `EXCLUDED_SRCS` to include `Foo.y`, then `Foo.hs` will also be excluded.

`EXTRA_SRCS`

Set to a list of extra source files (perhaps in directories not listed in `ALL_DIRS`) that should be considered.

The results of the automatic source file search are placed in the following make variables:

`SRCS`

All source files found, sorted and without duplicates, including those which might not exist yet but will be derived from other existing sources. `SRCS` *can* be overriden if necessary, in which case the variables below will follow suit.

`HS_SRCS`

all Haskell source files in the current directory, including those derived from other source files (eg. Happy sources also give rise to Haskell sources).

`HS_OBJS`

Object files derived from `HS_SRCS`.

`HS_IFACES`

Interface files (`.hi` files) derived from `HS_SRCS`.

`C_SRCS`

All C source files found.

`C_OBJS`

Object files derived from `C_SRCS`.

`SCRIPT_SRCS`

All script source files found (`.lprl` files).

`SCRIPT_OBJS`

"object" files derived from `SCRIPT_SRCS` (`.prl` files).

`HSC_SRCS`

All `hsc2hs` source files (`.hsc` files).

`HAPPY_SRCS`

All `happy` source files (`.y` or `.hy` files).

`OBJS`

the concatenation of `$(HS_OBJS)`, `$(C_OBJS)`, and `$(SCRIPT_OBJS)`.

Any or all of these definitions can easily be overriden by giving new definitions in your `Makefile`.

What, exactly, does `paths.mk` consider a "source file" to be? It's based on the file's suffix (e.g. `.hs`, `.lhs`, `.c`, `.hy`, etc), but this is the kind of detail that changes, so rather than enumerate the source suffices here the best thing to do is to look in `paths.mk`.

`opts.mk`

defines **make** variables for option strings to pass to each program. For example, it defines `HC_OPTS`, the option strings to pass to the Haskell compiler. See Section 8.6.

`suffix.mk`

defines standard pattern rules—see Section 8.6.

Any of the variables and pattern rules defined by the boilerplate file can easily be overridden in any particular `Makefile`, because the boilerplate `include` comes first. Definitions after this `include` directive simply override the default ones in `boilerplate.mk`.

8.6. Pattern rules and options

The file `suffix.mk` defines standard *pattern rules* that say how to build one kind of file from another, for example, how to build a `.o` file from a `.c` file. (GNU **make**'s *pattern rules* are more powerful and easier to use than Unix **make**'s *suffix rules*.)

Almost all the rules look something like this:

```
%.o : %.c
      $(RM) $@
      $(CC) $(CC_OPTS) -c $< -o $@
```

Here's how to understand the rule. It says that *something*`.o` (say `Foo.o`) can be built from *something*`.c` (`Foo.c`), by invoking the C compiler (path name held in `$(CC)`), passing to it the options `$(CC_OPTS)` and the rule's dependent file of the rule `$<` (`Foo.c` in this case), and putting the result in the rule's target `$@` (`Foo.o` in this case).

Every program is held in a **make** variable defined in `mk/config.mk`—look in `mk/config.mk` for the complete list. One important one is the Haskell compiler, which is called `$(HC)`.

Every program's options are are held in a **make** variables called `<prog>_OPTS`. the `<prog>_OPTS` variables are defined in `mk/opts.mk`. Almost all of them are defined like this:

```
CC_OPTS = $(SRC_CC_OPTS) $(WAY$(_way)_CC_OPTS) $($*_CC_OPTS) $(EXTRA_CC_OPTS)
```

The four variables from which `CC_OPTS` is built have the following meaning:

`SRC_CC_OPTS`:

options passed to all C compilations.

`WAY_<way>_CC_OPTS`:

options passed to C compilations for way `<way>`. For example, `WAY_mp_CC_OPTS` gives options to pass to the C compiler when compiling way `mp`. The variable `WAY_CC_OPTS` holds options to pass to the C compiler when compiling the standard way. (Section 8.9 dicusses multi-way compilation.)

`<module>_CC_OPTS`:

options to pass to the C compiler that are specific to module `<module>`. For example, `SMap_CC_OPTS` gives the specific options to pass to the C compiler when compiling `SMap.c`.

`EXTRA_CC_OPTS`:

extra options to pass to all C compilations. This is intended for command line use, thus:

```
gmake libHS.a EXTRA_CC_OPTS="-v"
```

8.7. The main `mk/target.mk` file

`target.mk` contains canned rules for all the standard targets described in Section 7.6. It is complicated by the fact that you don't want all of these rules to be active in every `Makefile`. Rather than have a plethora of tiny files which you can include selectively, there is a single file, `target.mk`, which selectively includes rules based on whether you have defined certain variables in your `Makefile`. This section explains what rules you get, what variables control them, and what the rules do. Hopefully, you will also get enough of an idea of what is supposed to happen that you can read and understand any weird special cases yourself.

`HS_PROG`.

If `HS_PROG` is defined, you get rules with the following targets:

`HS_PROG`

itself. This rule links `$(OBJS)` with the Haskell runtime system to get an executable called `$(HS_PROG)`.

`install`

installs `$(HS_PROG)` in `$(bindir)`.

`C_PROG`

is similar to `HS_PROG`, except that the link step links `$(C_OBJS)` with the C runtime system.

`LIBRARY`

is similar to `HS_PROG`, except that it links `$(LIB_OBJS)` to make the library archive `$(LIBRARY)`, and `install` installs it in `$(libdir)`.

`LIB_DATA`

...

`LIB_EXEC`

...

`HS_SRCS`, `C_SRCS`.

If `HS_SRCS` is defined and non-empty, a rule for the target `depend` is included, which generates dependency information for Haskell programs. Similarly for `C_SRCS`.

All of these rules are "double-colon" rules, thus

```
install :: $(HS_PROG)
      ...how to install it...
```

GNU **make** treats double-colon rules as separate entities. If there are several double-colon rules for the same target it takes each in turn and fires it if its dependencies say to do so. This means that you can, for example, define both `HS_PROG` and `LIBRARY`, which will generate two rules for `install`. When you type **gmake install** both rules will be fired, and both the program and the library will be installed, just as you wanted.

8.8. Recursion

In leaf `Makefile`s the variable `SUBDIRS` is undefined. In non-leaf `Makefile`s, `SUBDIRS` is set to the list of sub-directories that contain subordinate `Makefile`s. *It is up to you to set `SUBDIRS` in the `Makefile`.* There is no automation here—`SUBDIRS` is too important to automate.

When `SUBDIRS` is defined, `target.mk` includes a rather neat rule for the standard targets (Section 7.6 that simply invokes **make** recursively in each of the sub-directories.

These recursive invocations are guaranteed to occur in the order in which the list of directories is specified in `SUBDIRS`. This guarantee can be important. For example, when you say **gmake boot** it can be important that the recursive invocation of **make boot** is done in one sub-directory (the include files, say) before another (the source files). Generally, put the most independent sub-directory first, and the most dependent last.

8.9. Way management

We sometimes want to build essentially the same system in several different "ways". For example, we want to build GHC's `Prelude` libraries with and without profiling, so that there is an appropriately-built library archive to link with when the user compiles his program. It would be possible to have a completely separate build tree for each such "way", but it would be horribly bureaucratic, especially since often only parts of the build tree need to be constructed in multiple ways.

Instead, the `target.mk` contains some clever magic to allow you to build several versions of a system; and to control locally how many versions are built and how they differ. This section explains the magic.

The files for a particular way are distinguished by munging the suffix. The "normal way" is always built, and its files have the standard suffices `.o`, `.hi`, and so on. In addition, you can build one or more extra ways, each distinguished by a *way tag*. The object files and interface files for one of these extra ways are distinguished by their suffix. For example, way `mp` has files `.mp_o` and `.mp_hi`. Library archives have their way tag the other side of the dot, for boring reasons; thus, `libHS_mp.a`.

A **make** variable called `way` holds the current way tag. *`way` is only ever set on the command line of **gmake*** (usually in a recursive invocation of **gmake** by the system). It is never set inside a `Makefile`. So it is a global constant for any one invocation of **gmake**. Two other **make** variables, `way_` and `_way` are immediately derived from `$(way)` and never altered. If `way` is not set, then neither are `way_` and `_way`, and the invocation of **make** will build the "normal way". If `way` is set, then the other two variables are set in sympathy. For example, if `$(way)` is "`mp`", then `way_` is set to "`mp_`" and `_way` is set to "`_mp`". These three variables are then used when constructing file names.

So how does **make** ever get recursively invoked with `way` set? There are two ways in which this happens:

- For some (but not all) of the standard targets, when in a leaf sub-directory, **make** is recursively invoked for each way tag in `$(WAYS)`. You set `WAYS` in the `Makefile` to the list of way tags you want these targets built for. The mechanism here is very much like the recursive invocation of **make** in sub-directories (Section 8.8). It is up to you to set `WAYS` in your `Makefile`; this is how you control what ways will get built.
- For a useful collection of targets (such as `libHS_mp.a`, `Foo.mp_o`) there is a rule which recursively invokes **make** to make the specified target, setting the `way` variable. So if you say **gmake Foo.mp_o** you should see a recursive invocation **gmake Foo.mp_o way=mp**, and *in this recursive invocation the pattern rule for compiling a Haskell file into a `.o` file will match*. The key pattern rules (in `suffix.mk`) look like this:

  ```
  %.$(way_)o : %.lhs
        $(HC) $(HC_OPTS) $< -o $@
  ```

  Neat, eh?
- You can invoke **make** with a particular `way` setting yourself, in order to build files related to a particular `way` in the current directory. eg.

```
$ make way=p
```

will build files for the profiling way only in the current directory.

8.10. When the canned rule isn't right

Sometimes the canned rule just doesn't do the right thing. For example, in the `nofib` suite we want the link step to print out timing information. The thing to do here is *not* to define `HS_PROG` or `C_PROG`, and instead define a special purpose rule in your own `Makefile`. By using different variable names you will avoid the canned rules being included, and conflicting with yours.

9. Building the documentation

9.1. Tools for building the Documentation

The following additional tools are required if you want to format the documentation that comes with the `fptools` projects:

DocBook

Much of our documentation is written in SGML, using the DocBook DTD. Instructions on installing and configuring the DocBook tools are below.

TeX

A decent TeX distribution is required if you want to produce printable documentation. We recomment teTeX, which includes just about everything you need.

Haddock

Haddock is a Haskell documentation tool that we use for automatically generating documentation from the library source code. It is an `fptools` project in itself. To build documentation for the libraries (`fptools/libraries`) you should check out and build Haddock in `fptools/haddock`. Haddock requires GHC to build.

9.2. Installing the DocBook tools

9.2.1. Installing the DocBook tools on Linux

If you're on a recent RedHat system (7.0+), you probably have working DocBook tools already installed. The configure script should detect your setup and you're away.

If you don't have DocBook tools installed, and you are using a system that can handle RedHat RPM packages, you can probably use the Cygnus DocBook tools (http://sourceware.cygnus.com/docbook-tools/), which is the most shrink-wrapped SGML suite that we could find. You need all the RPMs except for psgml (i.e. `docbook`, `jade`, `jadetex`, `sgmlcommon` and `stylesheets`). Note that most of these RPMs are architecture neutral, so are likely to be found in a `noarch` directory. The SuSE RPMs also work; the RedHat ones *don't* in RedHat 6.2 (7.0 and later should be OK), but they are easy to fix: just make a symlink from `/usr/lib/sgml/stylesheets/nwalsh-modular/lib/dblib.dsl` to `/usr/lib/sgml/lib/dblib.dsl`.

9.2.2. Installing DocBook on FreeBSD

On FreeBSD systems, the easiest way to get DocBook up and running is to install it from the ports tree or a pre-compiled package (packages are available from your local FreeBSD mirror site).

To use the ports tree, do this:

```
$ cd /usr/ports/textproc/docproj
$ make install
```

This installs the FreeBSD documentation project tools, which includes everything needed to format the GHC documentation.

9.2.3. Installing from binaries on Windows

It's a good idea to use Norman Walsh's installation notes (http://nwalsh.com/docbook/dsssl/doc/install.html) as a guide. You should get version 3.1 of DocBook, and note that his file `test.sgm` won't work, as it needs version 3.0. You should unpack Jade into `\Jade`, along with the entities, DocBook into `\docbook`, and the DocBook stylesheets into `\docbook\stylesheets` (so they actually end up in `\docbook\stylesheets\docbook`).

9.2.4. Installing the DocBook tools from source

9.2.4.1. Jade

Install OpenJade (http://openjade.sourceforge.net/) (Windows binaries are available as well as sources). If you want DVI, PS, or PDF then install JadeTeX from the `dsssl` subdirectory. (If you get the error:

```
! LaTeX Error: Unknown option implicit=false' for package hyperref'.
```

your version of **hyperref** is out of date; download it from CTAN (`macros/latex/contrib/supported/hyperref`), and make it, ensuring that you have first removed or renamed your old copy. If you start getting file not found errors when making the test for

hyperref, you can abort at that point and proceed straight to **make install**, or enter them as `../filename`.)

Make links from `virtex` to `jadetex` and `pdfvirtex` to `pdfjadetex` (otherwise DVI, PostScript and PDF output will not work). Copy `dsssl/*.{dtd,dsl}` and `catalog` to `/usr/[local/]lib/sgml`.

9.2.4.2. DocBook and the DocBook stylesheets

Get a Zip of DocBook (http://www.oasis-open.org/docbook/sgml/3.1/index.html) and install the contents in `/usr/[local/]/lib/sgml`.

Get the DocBook stylesheets (http://nwalsh.com/docbook/dsssl/) and install in `/usr/[local/]lib/sgml/stylesheets` (thereby creating a subdirectory docbook). For indexing, copy or link `collateindex.pl` from the DocBook stylesheets archive in `bin` into a directory on your `PATH`.

Download the ISO entities (http://www.oasis-open.org/cover/ISOEnts.zip) into `/usr/[local/]lib/sgml`.

9.3. Configuring the DocBook tools

Once the DocBook tools are installed, the configure script will detect them and set up the build system accordingly. If you have a system that isn't supported, let us know, and we'll try to help.

9.4. Remaining problems

If you install from source, you'll get a pile of warnings of the form

```
DTDDECL catalog entries are not supported
```

every time you build anything. These can safely be ignored, but if you find them tedious you can get rid of them by removing all the `DTDDECL` entries from `docbook.cat`.

9.5. Building the documentation

To build documentation in a certain format, you can say, for example,

```
$ make html
```

to build HTML documentation below the current directory. The available formats are: `dvi`, `ps`, `pdf`, `html`, and `rtf`. Note that not all documentation can be built in all of these formats: HTML

documentation is generally supported everywhere, and DocBook documentation might support the other formats (depending on what other tools you have installed).

All of these targets are recursive; that is, saying `make html` will make HTML docs for all the documents recursively below the current directory.

Because there are many different formats that the DocBook documentation can be generated in, you have to select which ones you want by setting the `SGMLDocWays` variable to a list of them. For example, in `build.mk` you might have a line:

```
SGMLDocWays = html ps
```

This will cause the documentation to be built in the requested formats as part of the main build (the default is not to build any documentation at all).

9.6. Installing the documentation

To install the documentation, use:

```
$ make install-docs
```

This will install the documentation into `$(datadir)` (which defaults to `$(prefix)/share`). The exception is HTML documentation, which goes into `$(datadir)/html`, to keep things tidy.

Note that unless you set `$(SGMLDocWays)` to a list of formats, the `install-docs` target won't do anything for SGML documentation.

10. Porting GHC

This section describes how to port GHC to a currenly unsupported platform. There are two distinct possibilities:

- The hardware architecture for your system is already supported by GHC, but you're running an OS that isn't supported (or perhaps has been supported in the past, but currently isn't). This is the easiest type of porting job, but it still requires some careful bootstrapping. Proceed to Section 10.1.
- Your system's hardware architecture isn't supported by GHC. This will be a more difficult port (though by comparison perhaps not as difficult as porting gcc). Proceed to Section 10.2.

10.1. Booting/porting from C (`.hc`) files

Bootstrapping GHC on a system without GHC already installed is achieved by taking the intermediate C files (known as HC files) from a GHC compilation on a supported system to the target machine, and compiling them using gcc to get a working GHC.

NOTE: GHC version 5.xx is significantly harder to bootstrap from C than previous versions. We recommend starting from version 4.08.2 if you need to bootstrap in this way.

HC files are architecture-dependent (but not OS-dependent), so you have to get a set that were generated on similar hardware. There may be some supplied on the GHC download page, otherwise you'll have to compile some up yourself, or start from *unregisterised* HC files - see Section 10.2.

The following steps should result in a working GHC build with full libraries:

- Unpack the HC files on top of a fresh source tree (make sure the source tree version matches the version of the HC files *exactly*!). This will place matching `.hc` files next to the corresponding Haskell source (`.hs` or `.lhs`) in the compiler subdirectory `ghc/compiler` and in the libraries (subdirectories of `hslibs` and `libraries`).
- The actual build process is fully automated by the `hc-build` script located in the `distrib` directory. If you eventually want to install GHC into the directory *`dir`*, the following command will execute the whole build process (it won't install yet):

  ```
  foo% distrib/hc-build --prefix=dir
  ```

  By default, the installation directory is `/usr/local`. If that is what you want, you may omit the argument to `hc-build`. Generally, any option given to `hc-build` is passed through to the configuration script `configure`. If `hc-build` successfully completes the build process, you can install the resulting system, as normal, with

  ```
  foo% make install
  ```

10.2. Porting GHC to a new architecture

The first step in porting to a new architecture is to get an *unregisterised* build working. An unregisterised build is one that compiles via vanilla C only. By contrast, a registerised build uses the following architecture-specific hacks for speed:

- Global register variables: certain abstract machine "registers" are mapped to real machine registers, depending on how many machine registers are available (see `ghc/includes/MachRegs.h`).
- Assembly-mangling: when compiling via C, we feed the assembly generated by gcc though a Perl script known as the *mangler* (see `ghc/driver/mangler/ghc-asm.lprl`). The mangler rearranges the assembly to support tail-calls and various other optimisations.

In an unregisterised build, neither of these hacks are used — the idea is that the C code generated by the compiler should compile using gcc only. The lack of these optimisations costs about a factor of two in performance, but since unregisterised compilation is usually just a step on the way to a full registerised port, we don't mind too much.

10.2.1. Building an unregisterised port

The first step is to get some unregisterised HC files. Either (a) download them from the GHC site (if there are some available for the right version of GHC), or (b) build them yourself on any machine with a working GHC. If at all possible this should be a machine with the same word size as the target.

There is a script available which should automate the process of doing the 2-stage bootstrap necessary to get the unregisterised HC files - it's available in `fptools/distrib/cross-port` (http://cvs.haskell.org/cgi-bin/cvsweb.cgi/fptools/distrib/cross-port) in CVS.

Now take these unregisterised HC files to the target platform and bootstrap a compiler from them as per the instructions in Section 10.1. In `build.mk`, you need to tell the build system that the compiler you're building is (a) unregisterised itself, and (b) builds unregisterised binaries. This varies depending on the GHC version you're bootstraping:

```
# build.mk for GHC 4.08.x
GhcWithRegisterised=NO

# build.mk for GHC 5.xx
GhcUnregisterised=YES
```

Version 5.xx only: use the option `--enable-hc-boot-unregisterised` instead of `--enable-hc-boot` when running `./configure`.

The build may not go through cleanly. We've tried to stick to writing portable code in most parts of the compiler, so it should compile on any POSIXish system with gcc, but in our experience most systems differ from the standards in one way or another. Deal with any problems as they arise - if you get stuck, ask the experts on `<glasgow-haskell-users@haskell.org>`.

Once you have the unregisterised compiler up and running, you can use it to start a registerised port. The following sections describe the various parts of the system that will need architecture-specific tweaks in order to get a registerised build going.

Lots of useful information about the innards of GHC is available in the GHC Commentary (http://www.cse.unsw.edu.au/~chak/haskell/ghc/comm/), which might be helpful if you run into some code which needs tweaking for your system.

10.2.2. Porting the RTS

The following files need architecture-specific code for a registerised build:

`ghc/includes/MachRegs.h`

> Defines the STG-register to machine-register mapping. You need to know your platform's C calling convention, and which registers are generally available for mapping to global register variables. There are plenty of useful comments in this file.

`ghc/includes/TailCalls.h`

> Macros that cooperate with the mangler (see Section 10.2.3) to make proper tail-calls work.

`ghc/rts/Adjustor.c`

Support for `foreign import "wrapper"` (aka `foreign export dynamic`). Not essential for getting GHC bootstrapped, so this file can be deferred until later if necessary.

`ghc/rts/StgCRun.c`

The little assembly layer between the C world and the Haskell world. See the comments and code for the other architectures in this file for pointers.

`ghc/rts/MBlock.h`
`ghc/rts/MBlock.c`

These files are really OS-specific rather than architecture-specific. In `MBlock.h` is specified the absolute location at which the RTS should try to allocate memory on your platform (try to find an area which doesn't conflict with code or dynamic libraries). In `Mblock.c` you might need to tweak the call to `mmap()` for your OS.

10.2.3. The mangler

The mangler is an evil Perl-script that rearranges the assembly code output from gcc to do two main things:

- Remove function prologues and epilogues, and all movement of the C stack pointer. This is to support tail-calls: every code block in Haskell code ends in an explicit jump, so we don't want the C-stack overflowing while we're jumping around between code blocks.
- Move the *info table* for a closure next to the entry code for that closure. In unregisterised code, info tables contain a pointer to the entry code, but in registerised compilation we arrange that the info table is shoved right up against the entry code, and addressed backwards from the entry code pointer (this saves a word in the info table and an extra indirection when jumping to the closure entry code).

The mangler is abstracted to a certain extent over some architecture-specific things such as the particular assembler directives used to herald symbols. Take a look at the definitions for other architectures and use these as a starting point.

10.2.4. The native code generator

The native code generator isn't essential to getting a registerised build going, but it's a desirable thing to have because it can cut compilation times in half. The native code generator is described in some detail in the GHC commentary (http://www.cse.unsw.edu.au/~chak/haskell/ghc/comm/).

10.2.5. GHCi

To support GHCi, you need to port the dynamic linker (`fptools/ghc/rts/Linker.c`). The linker currently supports the ELF and PEi386 object file formats - if your platform uses one of these then you probably don't have to do anything except fiddle with the `#ifdef`s at the top of `Linker.c` to tell it about your OS.

If your system uses a different object file format, then you have to write a linker — good luck!

11. Known pitfalls in building Glasgow Haskell

WARNINGS about pitfalls and known "problems":

1. One difficulty that comes up from time to time is running out of space in `TMPDIR`. (It is impossible for the configuration stuff to compensate for the vagaries of different sysadmin approaches to temp space.) The quickest way around it is **setenv TMPDIR /usr/tmp** or even **setenv TMPDIR .** (or the equivalent incantation with your shell of choice). The best way around it is to say

   ```
   export TMPDIR=<dir>
   ```

   in your `build.mk` file. Then GHC and the other `fptools` programs will use the appropriate directory in all cases.

2. In compiling some support-code bits, e.g., in `ghc/rts/gmp` and even in `ghc/lib`, you may get a few C-compiler warnings. We think these are OK.

3. When compiling via C, you'll sometimes get "warning: assignment from incompatible pointer type" out of GCC. Harmless.

4. Similarly, **ar**chiving warning messages like the following are not a problem:

   ```
   ar: filename GlaIOMonad__1_2s.o truncated to GlaIOMonad_
   ar: filename GlaIOMonad__2_2s.o truncated to GlaIOMonad_
   ...
   ```

5. In compiling the compiler proper (in `compiler/`), you *may* get an "Out of heap space" error message. These can vary with the vagaries of different systems, it seems. The solution is simple:

   - If you're compiling with GHC 4.00 or later, then the *maximum* heap size must have been reached. This is somewhat unlikely, since the maximum is set to 64M by default. Anyway, you can raise it with the `-optCrts-M<size>` flag (add this flag to `<module>_HC_OPTS` **make** variable in the appropriate `Makefile`).
   - For GHC < 4.00, add a suitable `-H` flag to the `Makefile`, as above.

and try again: **gmake**. (see Section 8.6 for information about `<module>_HC_OPTS`.) Alternatively, just cut to the chase:

```
% cd ghc/compiler
% make EXTRA_HC_OPTS=-optCrts-M128M
```

6. If you try to compile some Haskell, and you get errors from GCC about lots of things from `/usr/include/math.h`, then your GCC was mis-installed. **fixincludes** wasn't run when it should've been. As **fixincludes** is now automagically run as part of GCC installation, this bug also suggests that you have an old GCC.

7. You *may* need to re-**ranlib** your libraries (on Sun4s).

   ```
   % cd $(libdir)/ghc-x.xx/sparc-sun-sunos4
   % foreach i ( `find . -name '*.a' -print` ) # or other-shell equiv...
   ?    ranlib $i
   ?    # or, on some machines: ar s $i
   ? end
   ```

   We'd be interested to know if this is still necessary.

8. GHC's sources go through **cpp** before being compiled, and **cpp** varies a bit from one Unix to another. One particular gotcha is macro calls like this:

   ```
   SLIT("Hello, world")
   ```

   Some **cpp**s treat the comma inside the string as separating two macro arguments, so you get

   ```
   :731: macro `SLIT' used with too many (2) args
   ```

   Alas, **cpp** doesn't tell you the offending file! Workaround: don't put weird things in string args to **cpp** macros.

12. Notes for building under Windows

This section summarises how to get the utilities you need on your Win95/98/NT/2000 machine to use CVS and build GHC. Similar notes for installing and running GHC may be found in the user guide. In general, Win95/Win98 behave the same, and WinNT/Win2k behave the same. You should read the GHC installation guide sections on Windows (in the user guide) before continuing to read these notes.

12.1. Cygwin and MinGW

The Windows situation for building GHC is rather confusing. This section tries to clarify, and to establish terminology.

12.1.1. GHC-mingw

MinGW (Minimalist GNU for Windows) (http://www.mingw.org) is a collection of header files and import libraries that allow one to use **gcc** and produce native Win32 programs that do not rely on any third-party DLLs. The current set of tools include GNU Compiler Collection (**gcc**), GNU Binary Utilities (Binutils), GNU debugger (Gdb), GNU make, and a assorted other utilities.

The GHC that we distribute includes, inside the distribution itself, the MinGW **gcc**, **as**, **ld**, and a bunch of input/output libraries. GHC compiles Haskell to C (or to assembly code), and then invokes these MinGW tools to generate an executable binary. The resulting binaries can run on any Win32 system.

We will call a GHC that targets MinGW in this way *GHC-mingw*.

The down-side of GHC-mingw is that the MinGW libraries do not support anything like the full Posix interface. So programs compiled with GHC-mingw cannot import the (Haskell) Posix library; they have to do their input output using standard Haskell I/O libraries, or native Win32 bindings.

12.1.2. GHC-cygwin

There *is* a way to get the full Posix interface, which is to use Cygwin. Cygwin (http://www.cygwin.com) is a complete Unix simulation that runs on Win32. Cygwin comes with a shell, and all the usual Unix commands: **mv**, **rm**, **ls**, plus of course **gcc**, **ld** and so on. A C program compiled with the Cygwin **gcc** certainly can use all of Posix.

So why doesn't GHC use the Cygwin **gcc** and libraries? Because Cygwin comes with a DLL *that must be linked with every runnable Cygwin-compiled program*. A program compiled by the Cygwin tools cannot run at all unless Cygwin is installed. If GHC targeted Cygwin, users would have to install Cygwin just to run the Haskell programs that GHC compiled; and the Cygwin DLL would have to be in the DLL load path. Worse, Cygwin is a moving target. The name of the main DLL, `cygwin1.dll` does not change, but the implementation certainly does. Even the interfaces to functions it exports seem to change occasionally. So programs compiled by GHC might only run with particular versions of Cygwin. All of this seems very undesirable.

Nevertheless, it is certainly possible to build a version of GHC that targets Cygwin; we will call that *GHC-cygwin*. The up-side of GHC-cygwin is that Haskell programs compiled by GHC-cygwin can import the (Haskell) Posix library.

12.1.3. Summary

Notice that "GHC-mingw" means "GHC that *targets* MinGW". It says nothing about how that GHC was *built*. It is entirely possible to have a GHC-mingw that was built by compiling GHC's Haskell sources with a GHC-cygwin, or vice versa.

We distribute only a GHC-mingw built by a GHC-mingw; supporting GHC-cygwin too is beyond our resources. The GHC we distribute therefore does not require Cygwin to run, nor do the programs it compiles require Cygwin.

The instructions that follow describe how to build GHC-mingw. It is possible to build GHC-cygwin, but it's not a supported route, and the build system might be flaky.

12.2. Installing and configuring Cygwin

You don't need Cygwin to *use* GHC, but you do need it to *build* GHC.

Install Cygwin from http://www.cygwin.com/. The installation process is straightforward; we install it in `c:/cygwin`. Both **cvs** and **ssh** come with Cygwin, but you'll need them, so make sure you select them when running the Cygwin installer.

Now set the following user environment variables:

- Add `c:/cygwin/bin` and `c:/cygwin/usr/bin` to your `PATH`
- Set `MAKE_MODE` to `UNIX`. If you don't do this you get very weird messages when you type **make**, such as:

  ```
  /c: /c: No such file or directory
  ```

- Set `SHELL` to `c:/cygwin/bin/sh`. When you invoke a shell in Emacs, this `SHELL` is what you get.
- Set `HOME` to point to your home directory. This is where, for example, **bash** will look for your `.bashrc` file. Ditto **emacs** looking for `.emacsrc`

There are a few other things to do:

- Some script files used in the make system start with "**#!/bin/perl**", (and similarly for **bash**). Notice the hardwired path! So you need to ensure that your `/bin` directory has the following binaries in it:

  - **sh**
  - **perl**
  - **cat**

  All these come in Cygwin's `bin` directory, which you probably have installed as `c:/cygwin/bin`. By default Cygwin mounts "`/`" as `c:/cygwin`, so if you just take the defaults it'll all work ok. (You can discover where your Cygwin root directory `/` is by typing **mount**). Provided `/bin` points to the Cygwin `bin` directory, there's no need to copy anything.
- By default, cygwin provides the command shell `ash` as `sh.exe`. It has a couple of 'issues', so in your `/bin` directory, make sure that `bash.exe` is also provided as `sh.exe` (i.e. overwrite the old `sh.exe` with a copy of `bash.exe`).

Finally, here are some things to be aware of when using Cygwin:

- Cygwin doesn't deal well with filenames that include spaces. "`Program Files`" and "`Local files`" are common gotchas.
- Cygwin implements a symbolic link as a text file with some magical text in it. So other programs that don't use Cygwin's I/O libraries won't recognise such files as symlinks. In particular, programs compiled by GHC are meant to be runnable without having Cygwin, so they don't use the Cygwin library, so they don't recognise symlinks.
- Win32 has a **find** command which is not the same as Cygwin's find. You will probably discover that the Win32 **find** appears in your `PATH` before the Cygwin one, because it's in the *system* `PATH` environment variable, whereas you have probably modified the *user* `PATH` variable. You can always invoke **find** with an absolute path, or rename it.

12.3. Other things you need to install

You have to install the following other things to build GHC:

- Install an executable GHC, from http://www.haskell.org/ghc. This is what you will use to compile GHC. Add it in your `PATH`: the installer tells you the path element you need to add upon completion.
- Install an executable Happy, from http://www.haskell.org/happy. Happy is a parser generator used to compile the Haskell grammar. Add it in your `PATH`.
- GHC uses the *mingw* C compiler to generate code, so you have to install that. Just pick up a mingw bundle at http://www.mingw.org/. We install it in `c:/mingw`.
- Finally, check out a copy of GHC sources from the CVS repository, following the instructions above (Section 2.1).

12.4. Building GHC

OK! Now go read the documentation above on building from source (Section 7); the bullets below only tell you about Windows-specific wrinkles.

- Run **autoconf** both in `fptools` and in `fptools/ghc`. If you omit the latter step you'll get an error when you run `./configure`:

```
...lots of stuff...
creating mk/config.h
```

```
mk/config.h is unchanged
configuring in ghc
running /bin/sh ./configure  --cache-file=.././config.cache --srcdir=.
./configure: ./configure: No such file or directory
configure: error: ./configure failed for ghc
```

- **autoconf** seems to create the file `configure` read-only. So if you need to run autoconf again (which I sometimes do for safety's sake), you get

  ```
  /usr/bin/autoconf: cannot create configure: permission denied
  ```

  Solution: delete `configure` first.

- You either need to add `ghc` to your `PATH` before you invoke **configure**, or use the **configure** option `--with-ghc=c:/ghc/ghc-some-version/bin/ghc`.

- After **autoconf** run **./configure** in `fptools/` thus:

  ```
  ./configure --host=i386-unknown-mingw32 --with-gcc=/mingw/bin/gcc
  ```

  This is the point at which you specify that you are building GHC-mingw (see Section 12.1.1). Both these options are important! It's possible to get into trouble using the wrong C compiler!

  If you want to build GHC-cygwin (Section 12.1.2) you'll have to do something more like:

  ```
  ./configure --with-gcc=...the Cygwin gcc...
  ```

- Do not attempt to build the documentation. It needs all kinds of wierd Jade stuff that we haven't worked out for Win32.

Notes

1. One of the most important features of GNU **make** that we use is the ability for a `Makefile` to include another named file, very like **cpp**'s `#include` directive.